

3U55S2PR1FA

DIMENSIONS

Height	700 mm
Width	890 mm
Depth	340 mm

SPECIFICATIONS

Accessories (sold separately)

Central controller	Optional
--------------------	----------

Capacity

Cooling capacity (kW)	5.2 kW
Heating capacity (kW)	5 kW

Consumption

COP	4.39
EER	4.09
HSPF-RES (Hot/Average/Cold)	4.214/4.073/3.773
HSPFCOM (Hot/Average/Cold)	4.191/4.088/3.845

Star-Cool (Hot/Average/Cold)	4.5/3.5/3.5
Star-Heat (Hot/Average/Cold)	2.5/2.5/2.0
TCSPF-COM (Hot/Average/Cold)	8.622/9.004/12.894
TCSPF-RES (Hot/Average/Cold)	6.417/5.160/5.171

Features

Blue fin coils	•
Compressor type	Twin rotary
DRED (Demand Response) ready	Optional HPRT-DRA001
Inverter controlled compressor	•
MEPS approved	•
Refrigerant factory charge	1.4 kg
VEU approved	•

Installation

Maximum number indoor units	3
Pipe length maximum	50 m
Pipe size gas	3x 9.52mm
Pipe size liquid	3x 6.35mm

Performance

Airflow	3000m3/h
DC Inverter	•

Outdoor sound power SWL	64 dBA
Outdoor sound pressure SPL	51 dBA
R32 Refrigerant	•
Working temperature cooling	□-10°C to +46°C
Working temperature heating	□-15°C to +24°C

Power requirements

Minimum circuit amps	11.2 MCA
Power phase	Single phase
Supply frequency	50 Hz
Supply voltage	220-240 V

Product dimensions

Depth	340 mm
Height	700 mm
Net Weight	50 kg
Width	890 mm

Warranty

Parts and labour	5 years
------------------	---------

SKU	51626
-----	-------

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © 2020 Haier Inc. All rights reserved.

[Other product downloads available at haier.com](#)

- [↓](#) DWG
- [↓](#) DXF
- [↓](#) Installation Guide (English)

A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 0800 372273 W www.haier.com