

4U71S2PR1FA

DIMENSIONS

|        |        |
|--------|--------|
| Height | 700 mm |
| Width  | 890 mm |
| Depth  | 340 mm |

SPECIFICATIONS

Accessories (sold separately)

|                    |          |
|--------------------|----------|
| Central controller | Optional |
|--------------------|----------|

Capacity

|                       |        |
|-----------------------|--------|
| Cooling capacity (kW) | 7.1 kW |
| Heating capacity (kW) | 7.1 kW |

Consumption

|                             |                   |
|-----------------------------|-------------------|
| COP                         | 4.64              |
| EER                         | 4.25              |
| HSPF-RES (Hot/Average/Cold) | 4.845/4.565/4.152 |
| HSPFCOM (Hot/Average/Cold)  | 4.830/4.649/4.305 |

|                              |                   |
|------------------------------|-------------------|
| Star-Cool (Hot/Average/Cold) | 4.5/3.0/3.0       |
| Star-Heat (Hot/Average/Cold) | 3.0/3.0/2.5       |
| TCSPF-COM (Hot/Average/Cold) | 7.309/7.448/8.618 |
| TCSPF-RES (Hot/Average/Cold) | 6.142/4.995/4.973 |

Features

|                                |                      |
|--------------------------------|----------------------|
| Blue fin coils                 | •                    |
| Compressor type                | Twin rotary          |
| DRED (Demand Response) ready   | Optional HPRT-DRA001 |
| Inverter controlled compressor | •                    |
| MEPS approved                  | •                    |
| Refrigerant factory charge     | 2.2 kg               |
| VEU approved                   | •                    |

Installation

|                             |                     |
|-----------------------------|---------------------|
| Maximum number indoor units | 3                   |
| Pipe length maximum         | 70 m                |
| Pipe size gas               | 3x 9.52 + 1x 12.7mm |
| Pipe size liquid            | 3x 6.35mm           |

Performance

|         |          |
|---------|----------|
| Airflow | 4000m3/h |
|---------|----------|

|                             |                 |
|-----------------------------|-----------------|
| DC Inverter                 | •               |
| Outdoor sound power SWL     | 68 dBA          |
| Outdoor sound pressure SPL  | 55 dBA          |
| R32 Refrigerant             | •               |
| Working temperature cooling | □-10°C to +46°C |
| Working temperature heating | □-15°C to 24°C  |

Power requirements

|                      |              |
|----------------------|--------------|
| Minimum circuit amps | 15.3 MCA     |
| Power phase          | Single phase |
| Supply frequency     | 50 Hz        |
| Supply voltage       | 220-240 V    |

Product dimensions

|            |        |
|------------|--------|
| Depth      | 340 mm |
| Height     | 700 mm |
| Net Weight | 61 kg  |
| Width      | 890 mm |

Warranty

|                  |         |
|------------------|---------|
| Parts and labour | 5 years |
|------------------|---------|

|     |       |
|-----|-------|
| SKU | 51627 |
|-----|-------|

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © 2020 Haier Inc. All rights reserved.

[Other product downloads available at haier.com](#)

- [↓](#) DWG
- [↓](#) DXF
- [↓](#) Installation Guide (English)

#### **A PEACE OF MIND SALE**

**24 Hours 7 Days a Week Customer Support**

T 0800 372273 W [www.haier.com](http://www.haier.com)